



Bearing Code	d	D	B	rsmin	E	F	Mass (kg)	CrKN	CorKN	Limiting speed	D1min	D1max	D3min	D4max
NCF2926V	130	180	30	1.5	166.5	140.5	2.36	204	360	1600	138			172
NCF2928V	140	190	30	1.5	175	149	2.48	212	380	1500	148			182
NCF2930C	150	210	36	2	194.9	162.9	3.92	290	500	1300	159			201
NCF2932V	160	220	36	2	205	173	4.14	300	540	1200	169			211
NCF2934V	170	230	36	2	215.5	183.5	4.36	310	570	1100	179			221
NCF2936V	180	250	42	2	231.5	193.5	6.33	390	695	1000	189			241
NCF2938V	190	260	42	2	243.5	205.5	6.61	405	735	950	199			251
NCF2940V	200	280	48	2.1	262.4	220.4	9.29	490	915	850	210			270
NCF2944V	220	300	48	2.1	282.5	240.5	10.1	520	1000	800	230			290
NCF2948V	240	320	48	2.1	302.5	260.5	10.8	540	1080	700	250			310
NCF2952V	260	360	60	2.1	333.3	281.3	18.8	750	1430	670	270			350
NCF2956V	280	380	60	2.1	359	303	19.7	880	1730	600	290			370
NCF2960V	300	420	72	3	389.7	325.7	31.6	1120	2200	560	312			408
NCF2964V	320	440	72	3	410	346	33.5	1160	2360	530	332			428
NCF2968V	340	460	72	3	430.5	366.5	35.1	1200	2500	500	352			448
NCF2972V	360	480	72	3	451	387	37	1220	2600	480	372			468
NCF2976V	380	520	82	4	484.5	412.5	52.6	1460	3100	450	395			505
NCF2980V	400	540	82	4	507.5	435.5	54.9	1500	3250	450	415			525
NCF2984V	420	560	82	4	530	458	57.2	1530	3400	430	435			545
NCF2988V	440	600	95	4	565	481	80.7	2000	4400	400	455			585

NCF3024V	120	180	46	2	167.6	131.6	3.8	290	430	1600	128.8			171
NCF3028V	140	210	53	2	197.8	153.8	6.05	440	680	1300	148.8			201
NCF3030V	150	225	56	2.1	206.8	160.8	7.35	455	710	1200	160.2			114.8
NCF3032V	160	240	60	2.1	224.8	174.8	8.82	520	800	1100	160.2			114.8
NCF3034V	170	260	67	2.1	242.9	186.9	12.2	670	1060	1000	180.5			249.2
NCF3036V	180	280	74	2.1	260.2	200.2	16.1	780	1250	900	190.5			269.8
NCF3038V	190	290	75	2.1	269.8	209.8	17	800	1290	850	200.5			270
NCF3040V	200	310	82	2.1	287.8	223.8	21.8	915	1530	800	210.5			299.2
NCF3052V	260	400	104	4	376.1	286.1	44.7	1560	2600	600	275			385.4
NCF3056V	280	420	106	4	390.5	300.5	48.4	1630	2750	560	295			405.4
NJ2317VH	85	180	60	3	163	107	7.33	480	600	1800	99	106	119	166
NJ2318VH	90	190	64	3	165.3	105.3	8.82	520	655	1800	104	104	118	176
NJ2319VH	95	200	67	3	176.3	112.3	10.2	600	750	1700	109	111	125	186
NJ2320VH	100	215	73	3	187.3	119.3	13.1	655	830	1600	114	118	133	201
NJ2322VH	110	240	80	3	209.4	133.4	18.1	830	1060	1400	124	132	149	226
NJ2324VH	120	260	86	3	231.4	147.4	22.4	950	1220	1200	134	146	164	246
NJ2326VH	130	280	93	4	247.9	157.9	28.1	1100	1430	1000	147	156	176	263
NJ2328VH	140	300	102	4	264.5	168.5	35	1250	1630	1300	167	180	203	303
NJ2330VH	150	320	108	4	286.5	182.5	42.6	1500	2000	900	167	180	203	303
NJ2334VH	170	360	120	4	319.6	203.6	63.2	1760	2400	800	187	201	227	343
NJ2338VH	190	400	132	5	352.6	224.6	80.3	2080	2900	700	210	222	250	380
NJ2340VH	200	420	138	5	374.7	238.7	92	2320	3250	670	220	236	266	400
NJ2344VH	220	460	145	5	407.6	267.6	117	2650	3800	600	240	265	296	440